

italian
quality



Made in Italy

Industria
Leader

SIRENA S.p.A.

**Linea
acustico/
luminosa**

**Acoustic/
luminous
range**

HVS.

PRECONISATEUR DE SOLUTIONS DEPUIS 1985

2 rue René Laennec 51500 Taissy France
Fax: 03 26 85 19 08, Tel : 03 26 82 49 29

E-mail: hvssystem@hvssystem.com
Site web : www.hvssystem.com



Dispositivi di segnalazione acustico/luminosa a led integrati

Led integrated double warning signals - audible/visual

V 24 $\overline{\sim}$ -48 $\overline{\sim}$ -110 \sim -240 \sim ($\pm 10\%$)	$\overline{\sim}$ \sim 50/60 Hz	Flash/min. 0-150 ± 20	IP 30
On ∞	On ∞	1 2 3 4 5 6	PC autoestinguente self-extinguishing

Luce lampeggiante (fissa) - suono intermittente (continuo)


Flashing (continuous) light - intermittent (continuous) sound



LD 085 CTL A 600
LD085CTLA600

(B)

V $\overline{\sim}$	24	48	-	-
V \sim			110	240
$\bullet \bullet \bullet$ mA	70	65	20	20
$\bullet \circ$ mA	70	70	20	20
dB(A)1m	65	65	65	65
Hz 3600	F/m 110	F/m 110	F/m 0	F/m 0



Kg. 0,09


LD085CTLA60024DA1	66001	LD085CTLA60048DA1	66011	LD085CTLA600110A1	66021	LD085CTLA600240A1	66031
LD085CTLA60024DA2	66002	LD085CTLA60048DA2	66012	LD085CTLA600110A2	66022	LD085CTLA600240A2	66032
LD085CTLA60024DA3	66003	LD085CTLA60048DA3	66013	LD085CTLA600110A3	66023	LD085CTLA600240A3	66033
LD085CTLA60024DA4	66004	LD085CTLA60048DA4	66014	LD085CTLA600110A4	66024	LD085CTLA600240A4	66034
LD085CTLA60024DA5	66005	LD085CTLA60048DA5	66015	LD085CTLA600110A5	66025	LD085CTLA600240A5	66035
LD085CTLA60024DA6	66006	LD085CTLA60048DA6	66016	LD085CTLA600110A6	66026	LD085CTLA600240A6	66036



LD 165 CTL A 900
LD165CTLA900

(B)

V $\overline{\sim}$	24	48	-	-
V \sim			110	240
$\bullet \bullet \bullet$ mA	90	100	20	20
$\bullet \circ$ mA	90	80	20	20
dB(A)1m	72	72	72	72
Hz 2700	F/m 110	F/m 110	F/m 0	F/m 0



Kg. 0,21


LD165CTLA90024DA1	66041	LD165CTLA90048DA1	66051	LD165CTLA900110A1	66061	LD165CTLA900240A1	66071
LD165CTLA90024DA2	66042	LD165CTLA90048DA2	66052	LD165CTLA900110A2	66062	LD165CTLA900240A2	66072
LD165CTLA90024DA3	66043	LD165CTLA90048DA3	66053	LD165CTLA900110A3	66063	LD165CTLA900240A3	66073
LD165CTLA90024DA4	66044	LD165CTLA90048DA4	66054	LD165CTLA900110A4	66064	LD165CTLA900240A4	66074
LD165CTLA90024DA5	66045	LD165CTLA90048DA5	66055	LD165CTLA900110A5	66065	LD165CTLA900240A5	66075
LD165CTLA90024DA6	66046	LD165CTLA90048DA6	66056	LD165CTLA900110A6	66066	LD165CTLA900240A6	66076



LD 245 CTL A 1200
LD245CTLA1200

(B)

V $\overline{\sim}$	24	48	-	-
V \sim			110	240
$\bullet \bullet \bullet$ mA	105	120	20	20
$\bullet \circ$ mA	105	95	20	20
dB(A)1m	85	85	85	85
Hz 3600	F/m 110	F/m 110	F/m 0	F/m 0



Kg. 0,29

LD245CTLA120024DA1	66081	LD245CTLA120048DA1	66091	LD245CTLA1200110A1	66101	LD245CTLA1200240A1	66111
LD245CTLA120024DA2	66082	LD245CTLA120048DA2	66092	LD245CTLA1200110A2	66102	LD245CTLA1200240A2	66112
LD245CTLA120024DA3	66083	LD245CTLA120048DA3	66093	LD245CTLA1200110A3	66103	LD245CTLA1200240A3	66113
LD245CTLA120024DA4	66084	LD245CTLA120048DA4	66094	LD245CTLA1200110A4	66104	LD245CTLA1200240A4	66114
LD245CTLA120024DA5	66085	LD245CTLA120048DA5	66095	LD245CTLA1200110A5	66105	LD245CTLA1200240A5	66115
LD245CTLA120024DA6	66086	LD245CTLA120048DA6	66096	LD245CTLA1200110A6	66106	LD245CTLA1200240A6	66116

Dispositivi di segnalazione acustico/luminosa

Double warning signals-audible/visual

V 12-24-48-110-240 (±10%)	==	~ 50/60 Hz	Flash/min. 110±20-0	IP 30	
	°C -30 +50	On		1 2 3 4 5 6	PC autoestinguente self-extinguishing

Luce lampeggiante (e fissa) - suono intermittente (e continuo)

Flashing (and continuous) light - intermittent (and continuous) sound




CTL A 1200 FCL
CTLA1200FCL

ⓑ

	V ==	12	24	48	-	-
	V ~				110	240
	A	2.2	1.06	0.52	0.22	0.10
	Cd (p)	450	500	500	50	80
	dB(A)1m	85	85	85	85	85
	Hz 3600				F/m 110	

CTLA1200FCL12DA1 ● 33771	CTLA1200FCL24DA5 ● 33785	CTLA1200FCL110A3 ● 33803
CTLA1200FCL12DA2 ● 33772	CTLA1200FCL24DA6 ○ 33786	CTLA1200FCL110A4 ● 33804
CTLA1200FCL12DA3 ● 33773	CTLA1200FCL48DA1 ● 33791	CTLA1200FCL110A5 ● 33805
CTLA1200FCL12DA4 ● 33774	CTLA1200FCL48DA2 ● 33792	CTLA1200FCL110A6 ○ 33806
CTLA1200FCL12DA5 ● 33775	CTLA1200FCL48DA3 ● 33793	CTLA1200FCL240A1 ● 33821
CTLA1200FCL12DA6 ○ 33776	CTLA1200FCL48DA4 ● 33794	CTLA1200FCL240A2 ● 33822
CTLA1200FCL24DA1 ● 33781	CTLA1200FCL48DA5 ● 33795	CTLA1200FCL240A3 ● 33823
CTLA1200FCL24DA2 ● 33782	CTLA1200FCL48DA6 ○ 33796	CTLA1200FCL240A4 ● 33824
CTLA1200FCL24DA3 ● 33783	CTLA1200FCL110A1 ● 33801	CTLA1200FCL240A5 ● 33825
CTLA1200FCL24DA4 ● 33784	CTLA1200FCL110A2 ● 33802	CTLA1200FCL240A6 ○ 33826



Kg. 0,29

V 12÷24-110-240 (±10%)	==	~ 50/60 Hz	J 2-6	Flash/min. 1F: 65±10 - 2F: 2x 65±10	IP 30			°C -10 +40	On		1 2 3 4 5 6	PC autoestinguente self-extinguishing
------------------------	----	------------	-------	-------------------------------------	-------	--	--	------------	----	--	-------------	---------------------------------------

Luce a flash - suono intermittente

Xenon flashing light - intermittent sound

	1F	V ==	12÷24	-	-
	V ~			110	240
	mA	405	355	70	45
	Cd (p)	1200	1200	1400	1500
	dB(A)1m	75	75	72	68
	Hz 3700				F/m 65

	2F	V ==	12÷24	-	-
	V ~			110	240
	mA	355	355	85	40
	Cd (p)	650	700	1000	850
	400	500	700	600	
	dB(A)1m	75	75	72	68
Hz 3700				F/m 65	

	1F	V ==	12÷24	-	-
	V ~			110	240
	A	1.0	0.75	0.10	0.09
	Cd (p)	3150	3450	2700	3500
	dB(A)1m	80	80	75	72
	Hz 3700				F/m 65


	2F	V ==	12÷24	-	-
	V ~			110	240
	A	1.0	0.65	0.08	0.08
	Cd (p)	1750	1750	2000	2850
	1400	1400	1000	1900	
	dB(A)1m	80	80	75	72
Hz 3700				F/m 65	



CTL XA 1200
CTLXA1200J1F
CTLXA1200J2F
CTLXA1200J1F
CTLXA1200J2F

ⓑ

CTLXA1200J1F1224DA1 ● 27456	CTLXA1200J2F110A3 ● 27512	CTLXA1200J2F1224DA1 ● 27528
CTLXA1200J1F1224DA2 ● 27457	CTLXA1200J2F240A1 ● 27522	CTLXA1200J2F1224DA2 ● 27529
CTLXA1200J1F1224DA3 ● 27458	CTLXA1200J2F240A2 ● 27517	CTLXA1200J2F1224DA3 ● 27530
CTLXA1200J1F1224DA5 ● 27460	CTLXA1200J2F240A3 ● 27518	CTLXA1200J2F1224DA4 ● 27531
CTLXA1200J1F110A1 ● 27462	CTLXA1200J2F240A4 ● 27525	CTLXA1200J2F1224DA5 ● 27532
CTLXA1200J1F110A2 ● 27463	CTLXA1200J2F240A5 ● 27526	CTLXA1200J2F1224DA6 ○ 27533
CTLXA1200J1F110A3 ● 27464	CTLXA1200J2F240A6 ○ 27527	CTLXA1200J2F110A2 ● 27535
CTLXA1200J1F240A2 ● 27469	CTLXA1200J1F1224DA2 ● 27481	CTLXA1200J2F110A3 ● 27536
CTLXA1200J1F240A3 ● 27470	CTLXA1200J1F1224DA3 ● 27482	CTLXA1200J2F240A1 ● 27546
CTLXA1200J1F240A6 ○ 27479	CTLXA1200J1F110A2 ● 27487	CTLXA1200J2F240A2 ● 27541
CTLXA1200J2F1224DA2 ● 27505	CTLXA1200J1F110A3 ● 27488	CTLXA1200J2F240A3 ● 27542
CTLXA1200J2F1224DA3 ● 27506	CTLXA1200J1F240A2 ● 27493	CTLXA1200J2F240A4 ● 27549
CTLXA1200J2F1224DA5 ● 27508	CTLXA1200J1F240A3 ● 27494	CTLXA1200J2F240A5 ● 27550
CTLXA1200J2F110A2 ● 27511	CTLXA1200J1F240A4 ● 27495	CTLXA1200J2F240A6 ○ 27551
	CTLXA1200J1F240A5 ● 27496	



Kg. 0,32

Versione nera disponibile a richiesta.
Black option available on request.

Dispositivi di segnalazione acustico/luminosa

Double warning signals-audible/visual

Luce lampeggiante (e fissa) - suono intermittente (e continuo)
Flashing (and continuous) light - intermittent (and continuous) sound




MICROLAMP A FCL
MLAFCL

13

V 12-24-48-110-240 (±10%)	==	~ 50/60 Hz	Flash/min. 0-130±20	IP 30	☐
°C -30 +50	On ∞	🔊	1 2 3 4 5 6 PC	autoestinguente self-extinguishing	

V ==	12	24	48	-	-
V ~				110	240
mA	420	215	105	45	20
Cd (p)	25	18	8	3	2
dB(A)1m	75	75	75	75	75
Hz 2700	🔊 F/m 130		🔊 F/m 0		



Kg. 0,19

MLAFCL12DA1 ● 79721	MLAFCL24DA3 ● 79733	MLAFCL48DA5 ● 79745	MLAFCL240A1 ● 79771
MLAFCL12DA2 ● 79722	MLAFCL24DA4 ● 79734	MLAFCL48DA6 ○ 79746	MLAFCL240A2 ● 79772
MLAFCL12DA3 ● 79723	MLAFCL24DA5 ● 79735	MLAFCL110A1 ● 79751	MLAFCL240A3 ● 79773
MLAFCL12DA4 ● 79724	MLAFCL24DA6 ○ 79736	MLAFCL110A2 ● 79752	MLAFCL240A4 ● 79774
MLAFCL12DA5 ● 79725	MLAFCL48DA1 ● 79741	MLAFCL110A3 ● 79753	MLAFCL240A5 ● 79775
MLAFCL12DA6 ○ 79726	MLAFCL48DA2 ● 79742	MLAFCL110A4 ● 79754	MLAFCL240A6 ○ 79776
MLAFCL24DA1 ● 79731	MLAFCL48DA3 ● 79743	MLAFCL110A5 ● 79755	
MLAFCL24DA2 ● 79732	MLAFCL48DA4 ● 79744	MLAFCL110A6 ○ 79756	

Dispositivi di segnalazione acustico/luminosa a led integrati

Led integrated double warning signals-audible/visual

Luce lampeggiante (fissa) - suono intermittente (continuo)
Flashing (continuous) light - intermittent (continuous) sound




LD 125 MICRO A
LD125MCA

13

V 24 ~ 48 ~ 110 ~ 240 (±10%)	==	~ 50/60 Hz	Flash/min. 0-150±20	IP 30	☐
°C -30 +50	On ∞	🔊	1 2 3 4 5 6 PC	autoestinguente self-extinguishing	

V ==	24	48	-	-
V ~			110	240
●●● mA	90	65	20	20
●●○ mA	80	65	20	20
dB(A)1m	75	75	75	75
Hz 2700	🔊 F/m 130		🔊 F/m 0	



Kg. 0,19

LD125MCA24DA1 ● 66121	LD125MCA48DA1 ● 66131	LD125MCA110A1 ● 66141	LD125MCA240A1 ● 66151
LD125MCA24DA2 ● 66122	LD125MCA48DA2 ● 66132	LD125MCA110A2 ● 66142	LD125MCA240A2 ● 66152
LD125MCA24DA3 ● 66123	LD125MCA48DA3 ● 66133	LD125MCA110A3 ● 66143	LD125MCA240A3 ● 66153
LD125MCA24DA4 ● 66124	LD125MCA48DA4 ● 66134	LD125MCA110A4 ● 66144	LD125MCA240A4 ● 66154
LD125MCA24DA5 ● 66125	LD125MCA48DA5 ● 66135	LD125MCA110A5 ● 66145	LD125MCA240A5 ● 66155
LD125MCA24DA6 ○ 66126	LD125MCA48DA6 ○ 66136	LD125MCA110A6 ○ 66146	LD125MCA240A6 ○ 66156

Dispositivi di segnalazione acustico/luminosa

Double warning signals-audible/visual

Luce a flash - suono intermittente
Xenon flashing light - intermittent sound




MICROXENOLAMP A
MXLA1J1F
MXLA1J2F

13

V 12-24-48-110-240 (±10%)	==	~ 50/60 Hz	Flash/min. 0-130±20	IP 30	☐
°C -30 +50	On ∞	🔊	1 2 3 4 5 6 PC	autoestinguente self-extinguishing	

1F	V ==	12÷24	-	-	2F	V ==	12÷24	-	-		
	V ~		110	240		V ~		110	240		
	mA	205	165	50	50		mA	205	165	75	70
	Cd (p)	350	450	350	850		Cd (p)	350	450	350	850
	dB(A)1m	80	80	80	80		dB(A)1m	80	80	80	80
Xenon 1J LRX 1J	Hz 3000±500	🔊 F/m 65				Xenon 1J LRX 1J	Hz 3000±500	🔊 F/m 65			



Kg. 0,19

MXLA1F1224DA2 ● 91661	MXLA1F110A5 ● 91676	MXLA2F1224DA3 ● 91692	MXLA2F240A1 ● 91714
MXLA1F1224DA3 ● 91662	MXLA1F240A2 ● 91679	MXLA2F1224DA4 ● 91693	MXLA2F240A2 ● 91709
MXLA1F1224DA4 ● 91663	MXLA1F240A3 ● 91680	MXLA2F1224DA5 ● 91694	MXLA2F240A3 ● 91710
MXLA1F1224DA5 ● 91664	MXLA1F240A4 ● 91681	MXLA2F1224DA6 ○ 91695	MXLA2F240A4 ● 91717
MXLA1F1224DA6 ○ 91665	MXLA1F240A5 ● 91682	MXLA2F110A2 ● 91703	MXLA2F240A5 ● 91712
MXLA1F110A2 ● 91673	MXLA2F1224DA1 ● 91690	MXLA2F110A3 ● 91704	MXLA2F240A6 ○ 91719
MXLA1F110A3 ● 91674	MXLA2F1224DA2 ● 91691	MXLA2F110A5 ● 91706	

Versione nera disponibile a richiesta.
 Black option available on request.

Linea acustico/luminosa . Acoustic/luminous range

Avvisatori acustico/luminosi industriali

Double warning signals-audible/visual

Luce fissa - suono continuo
Continuous light - continuous sound




SLEM F
SLEMF
 (12)

V 12-24-48-110-240 (±10%)	50/60 Hz	IP 43	On	Hz (≈) 650±50
Hz (≈) 300÷7000	°C -30 +50	1 2 3 4 5 6	PC	autoestinguente self-extinguishing

BA 15d 5W LR BA 15d 5W	V ---	12	24	48	110	240
	mA	480	250	130	55	30
	Cd (p)	4	3	3	2.5	2.5
	mA	880	470	250	115	60
BA 15d 10W LR BA 15d 10W	Cd (p)	6	5	5	4	4
	dB(A)	96	96	96	96	96
	Hz	650±50				

BA 15d 5W LR BA 15d 5W	V ~	12	24	48	110	240
	mA	550	350	210	100	60
	Cd (p)	4	3	3	2.5	2.5
	A	1	0.6	0.33	0.15	0.08
BA 15d 10W LR BA 15d 10W	Cd (p)	6	5	5	4	4
	dB(A)	92	92	92	92	92
	Hz	300÷7000				



Kg. 0,25

SLEMF12D2	40622	SLEMF24A4	40714	SLEMF110A4	40694
SLEMF12D3	40623	SLEMF48D2	40662	SLEMF240D2	40412
SLEMF12D4	40624	SLEMF48D3	40663	SLEMF240D3	40413
SLEMF12A2	40632	SLEMF48D4	40664	SLEMF240D4	40414
SLEMF12A3	40633	SLEMF48A2	40672	SLEMF240A1	40721
SLEMF12A4	40634	SLEMF48A3	40673	SLEMF240A2	40422
SLEMF24D2	40352	SLEMF48A4	40674	SLEMF240A3	40703
SLEMF24D3	40643	SLEMF110D2	40682	SLEMF240A4	40704
SLEMF24D4	40644	SLEMF110D3	40683	SLEMF240A5	40705
SLEMF24A1	40711	SLEMF110D4	40684	SLEMF240A6	40706
SLEMF24A2	40712	SLEMF110A2	40692		
SLEMF24A3	40713	SLEMF110A3	40693		

Luce lampeggiante - suono continuo
Flashing light - continuous sound




SLEM L
SLEML
 (12)

Flash/min. 110±20

BA 15d 5W LR BA 15d 5W	V ---	12 ÷ 24 ÷ 48		
	mA	480	250	130
	Cd (p)	4	3	3
	mA	880	470	250
BA 15d 10W LR BA 15d 10W	Cd (p)	6	5	5
	dB(A)	96	96	96
	Hz	650±50		

BA 15d 5W LR BA 15d 5W	V ~	24 ÷ 48 ÷ 110 ÷ 240			
	mA	350	210	100	60
	Cd (p)	4	3	3	3
	mA	600	330	150	80
BA 15d 10W LR BA 15d 10W	Cd (p)	5	5	4	4
	dB(A)	92	92	92	92
	Hz	300÷7000			



Kg. 0,25

SLEML12D2	40322	SLEML24A3	40353	SLEML48A4	40374
SLEML12D3	40323	SLEML24A4	40354	SLEML110A2	40392
SLEML12D4	40324	SLEML48D2	40362	SLEML110A3	40393
SLEML24D2	40342	SLEML48D3	40363	SLEML110A4	40394
SLEML24D3	40343	SLEML48D4	40364	SLEML240A2	40702
SLEML24D4	40344	SLEML48A2	40372	SLEML240A3	40423
SLEML24A2	40642	SLEML48A3	40373	SLEML240A4	40424

Possibilità di installazione lampada a LED. LED bulb option.

Avvisatori acustico/luminosi a led integrati

Led integrated double warning signals-audible/visual

V $\overline{\overline{\overline{\sim}}}$ 24 48	V \sim 24 48 110 240	==	~ 50/60 Hz	IP 43	□
24 \sim 48 \sim					
°C -30 +50	On ∞		1 2 3 4 5 6	PC	autoestinguente self-extinguishing

Luce fissa - suono continuo

Continuous light - continuous sound




LD 125 SLEM F
LD125SLEM F

12

V $\overline{\overline{\overline{\sim}}}$	24	48	V \sim	24	48	110	240		
mA	130	85	mA	280	145	50	40		
	mA	120	85		mA	270	145	50	40
	dB(A)1m	96	96		dB(A)1m	92	92	92	92
Hz	650±50		Hz	300÷7000					

LD125SLEMF24D2		40562	LD125SLEMF48A2		40592
LD125SLEMF24D3		40563	LD125SLEMF48A3		40593
LD125SLEMF24D4		40564	LD125SLEMF48A4		40594
LD125SLEMF24A2		40572	LD125SLEMF110A2		40602
LD125SLEMF24A3		40573	LD125SLEMF110A3		40603
LD125SLEMF24A4		40574	LD125SLEMF110A4		40604
LD125SLEMF48D2		40582	LD125SLEMF240A2		40612
LD125SLEMF48D3		40583	LD125SLEMF240A3		40613
LD125SLEMF48D4		40584	LD125SLEMF240A4		40614



Kg. 0,25

Luce lampeggiante - suono continuo

Flashing light - continuous sound




LD 125 SLEM L
LD125SLEM L

12

V $\overline{\overline{\overline{\sim}}}$	24	48	V \sim	24	48	110	240		
mA	130	85	mA	280	145	50	40		
	mA	120	85		mA	270	145	50	40
	dB(A)1m	96	96		dB(A)1m	92	92	92	92
Hz	650±50		Hz	300÷7000					

LD125SLEM L24D2		40502	LD125SLEM L48A2		40532
LD125SLEM L24D3		40503	LD125SLEM L48A3		40533
LD125SLEM L24D4		40504	LD125SLEM L48A4		40534
LD125SLEM L24A2		40512	LD125SLEM L110A2		40542
LD125SLEM L24A3		40513	LD125SLEM L110A3		40543
LD125SLEM L24A4		40514	LD125SLEM L110A4		40544
LD125SLEM L48D2		40522	LD125SLEM L240A2		40552
LD125SLEM L48D3		40523	LD125SLEM L240A3		40553
LD125SLEM L48D4		40524	LD125SLEM L240A4		40554



Kg. 0,25

Flash/min. 150±20

Avvisatori acustico/luminosi industriali

Double warning signals-audible/visual

Luce a flash - suono continuo
Xenon flashing light - continuous sound




SLEM X
SLEM X

12

V 24-110-240 (±10%)	50/60 Hz	J 2 2 F	Flash/min. 65±10	IP 43	On ∞
Hz (---) 650±50	Hz (∞) 300÷7000	°C -30 +40	autoestinguente self-extinguishing		

Xenon 2J LRX 2J	V ---	24	V ~	24	110	240
	mA	350	mA	500	80	70
	Cd (p)	200	Cd (p)	200	75	120
		100		100	35	90
	dB(A)1m	96	dB(A)1m	92	92	92
	Hz	650±50		Hz	300÷7000	

SLEM X 24D2	40432	SLEM X 110A2	40452
SLEM X 24D3	40433	SLEM X 110A3	40453
SLEM X 24D4	40434	SLEM X 110A4	40454
SLEM X 24A2	40442	SLEM X 240A2	40462
SLEM X 24A3	40443	SLEM X 240A3	40463
SLEM X 24A4	40444	SLEM X 240A4	40464



Kg. 0,25

Dispositivo di segnalazione acustico/luminosa a led


Led double warning signal-audible/visual

Luce lampeggiante - 32 suoni (divisi in 2 canali per la selezione di 2 suoni in contemporanea)
Flashing light - 32 sounds (divided in two channels to select two sounds simultaneously)



SUPERVOLUX
SUPERVOLUX

13



Kg. 0,30

V ---	12	24
V ~	300	225
mA ---	615	545
dB(A)1m	94.5	96
dB(A)1m	97	98.5

SUPERVOLUX1224DA1	31481
SUPERVOLUX1224DA2	31482
SUPERVOLUX1224DA3	31483
SUPERVOLUX1224DA4	31484
SUPERVOLUX1224DA5	31485
SUPERVOLUX1224DA6	31486

V 12/24 (±10%)	50/60 Hz	Flash/min. 110±10
IP 65	°C -30 +50	On ∞
autoestinguente self-extinguishing		

TIPO DI SUONO SOUND TYPE	Frequenza (Hz) Frequency (Hz)
	Lineare / Linear
Bitonale / Bi-tone	600/700
Pluritonale / Multi-tone	1000/1700
Modulato / Modulated	1000/1700
Modulato / Modulated	1400/1600
Bitonale Veloce Fast Bi-tone	800/970
Pluritonale Veloce Fast Multi-tone	800÷970
Pluritonale Lento Slow Multi-tone	800÷970
Lineare / Linear	2850
Pluritonale Veloce Fast Multi-tone	2400÷2850
Pluritonale Lento Slow Multi-tone	2400÷2850
Pluritonale Intermittente Intermittent Multi-tone	500-1200
Pluritonale Discendente Descending Multi-tone	1200-500
Bitonale / Bi-tone	2400-2850
Intermittente Lento Slow Intermittent	970
Bitonale / Bi-tone	800/970

TIPO DI SUONO SOUND TYPE	Frequenza (Hz) Frequency (Hz)
	Intermittente / Intermittent
Intermittente / Intermittent	660
Intermittente Lento Slow Intermittent	660
Lineare / Linear	500
Bitonale / Bi-tone	440-550
Intermittente / Intermittent	660
Intermittente Veloce Fast Intermittent	2850
Pluritonale (Buzzer) Multi-tone (Buzzer)	800÷970
Pluritonale (Buzzer) Multi-tone (Buzzer)	2400÷2850
Intermittente Veloce Fast Intermittent	2850
Lineare / Linear	300
Bitonale con pausa Bi-tone with pause	600-700
Bitonale con pausa Bi-tone with pause	1200-1700
Bitonale con pausa Bi-tone with pause	2400-2850
Bitonale / Bi-tone	600-700
Evacuazione / Evacuation	440-560

Linea acustico/luminosa . Acoustic/luminous range

Dispositivi di segnalazione acustico/luminosa

Double warning signals-audible/visual

V 12-24-48-110-240 (±10%)	==	~ 50/60 Hz	Flash/min. 130±20	IP 30
☐	🎵	🔊	°C -30 +40	On ∞ autoestinguente self-extinguishing
 PC				




SIRLAMP MS 5
SIRLMS5

⑧

 BA 15d 5W LR BA 15d 5W	V ==	12	24	-	-	-
	V ~			48	110	240
	mA	770	585	250	120	60
	Cd (p)	25	18	3	2	2
	dB(A)1m	Min. 86.5 - Max 97				

SIRLMS512DA1 ● 40001	SIRLMS524DA3 ● 40013	SIRLMS548A5 ● 40045	SIRLMS5240A1 ● 40061
SIRLMS512DA2 ● 40002	SIRLMS524DA4 ● 40014	SIRLMS548A6 ○ 40046	SIRLMS5240A2 ● 40062
SIRLMS512DA3 ● 40003	SIRLMS524DA5 ● 40015	SIRLMS5110A1 ● 40051	SIRLMS5240A3 ● 40063
SIRLMS512DA4 ● 40004	SIRLMS524DA6 ○ 40016	SIRLMS5110A2 ● 40052	SIRLMS5240A4 ● 40064
SIRLMS512DA5 ● 40005	SIRLMS548A1 ● 40041	SIRLMS5110A3 ● 40053	SIRLMS5240A5 ● 40065
SIRLMS512DA6 ○ 40006	SIRLMS548A2 ● 40042	SIRLMS5110A4 ● 40054	SIRLMS5240A6 ○ 40066
SIRLMS524DA1 ● 40011	SIRLMS548A3 ● 40043	SIRLMS5110A5 ● 40055	
SIRLMS524DA2 ● 40012	SIRLMS548A4 ● 40044	SIRLMS5110A6 ○ 40056	



Kg. 0,87
BA Kg. 0,55

Dispositivi di segnalazione acustico/luminosa a led integrati

Led integrated double warning signals-audible/visual

Luce lampeggiante - suono intermittente (continuo)
Flashing light - intermittent (continuous) sound

V 24 ~ -48 ~ -110 ~ -240 ~ (±10%)	==	~ 50/60 Hz	Flash/min. 150±20	IP 30
☐	🎵	🔊	°C -30 +50	On ∞ autoestinguente self-extinguishing
 PC				


V ==	24	-	-	-	— Suono lineare / Single sound	Hz 1000	🎵
V ~		48	110	240	🔊 Suono bitonale / Bi-tone sound	Hz 600/700	🎵 F/m 150
●●● mA	460	210	90	55	🔊 Suono pluritonal / Multi-tone sound	Hz 1000÷1700	🎵 F/m 150
●●○ mA	450	210	90	55	🔊 Suono modulato / Modulated sound	Hz 1000÷1700	🎵 F/m 150
dB(A)1m	Min. 90 - Max 97				🔊 Suono alternativo / Alternative sound	Hz 440/550	🎵 F/m 150



LD 125 SIRLAMP MS 5
LD125SIRLMS5

⑫

LD125SIRLMS524DA1 ● 64951	LD125SIRLMS548A3 ● 64963	LD125SIRLMS5110A5 ● 64975
LD125SIRLMS524DA2 ● 64952	LD125SIRLMS548A4 ● 64964	LD125SIRLMS5110A6 ○ 64976
LD125SIRLMS524DA3 ● 64953	LD125SIRLMS548A5 ● 64965	LD125SIRLMS5240A1 ● 64981
LD125SIRLMS524DA4 ● 64954	LD125SIRLMS548A6 ○ 64966	LD125SIRLMS5240A2 ● 64982
LD125SIRLMS524DA5 ● 64955	LD125SIRLMS5110A1 ● 64971	LD125SIRLMS5240A3 ● 64983
LD125SIRLMS524DA6 ○ 64956	LD125SIRLMS5110A2 ● 64972	LD125SIRLMS5240A4 ● 64984
LD125SIRLMS548A1 ● 64961	LD125SIRLMS5110A3 ● 64973	LD125SIRLMS5240A5 ● 64985
LD125SIRLMS548A2 ● 64962	LD125SIRLMS5110A4 ● 64974	LD125SIRLMS5240A6 ○ 64986



Kg. 0,96

Dispositivi di segnalazione acustico/luminosa

Double warning signals-audible/visual

V 12÷24-110-240 (±10%)	50/60 Hz	Flash/min. 1F: 65±10 2F: 2x65±10	IP 30
		°C -30 +40	On ∞ autoestinguente self-extinguishing
		1 2 3 4 5 6	PC




SIRLAMP X 1F MS 5
SIRLAMP X 2F MS 5

SIRLX1FMS5
SIRLX2FMS5

ⓑ

1F	V \equiv	12÷24	-	-	2F	V \equiv	12÷24	-	-		
Xenon 1J LRX 1J	V \sim		110	240	Xenon 1J LRX 1J	V \sim		110	240		
	mA	550 530	115	80		mA	350 370	140	100		
	Cd (p)	350 450	350	750		Cd (p)	350 450	350	750		
	dB(A)1m	Min. 88.5 - Max 99.5				dB(A)	Min. 88.5 - Max 99.5				

SIRLX1FMS51224DA1 ● 40071	SIRLX1FMS5240A1 ● 40091	SIRLX2FMS5110A1 ● 40111
SIRLX1FMS51224DA2 ● 40072	SIRLX1FMS5240A2 ● 40092	SIRLX2FMS5110A2 ● 40112
SIRLX1FMS51224DA3 ● 40073	SIRLX1FMS5240A3 ● 40093	SIRLX2FMS5110A3 ● 40113
SIRLX1FMS51224DA4 ● 40074	SIRLX1FMS5240A4 ● 40094	SIRLX2FMS5110A4 ● 40114
SIRLX1FMS51224DA5 ● 40075	SIRLX1FMS5240A5 ● 40095	SIRLX2FMS5110A5 ● 40115
SIRLX1FMS51224DA6 ○ 40076	SIRLX1FMS5240A6 ○ 40096	SIRLX2FMS5110A6 ○ 40116
SIRLX1FMS5110A1 ● 40081	SIRLX2FMS51224DA1 ● 40101	SIRLX2FMS5240A1 ● 40121
SIRLX1FMS5110A2 ● 40082	SIRLX2FMS51224DA2 ● 40102	SIRLX2FMS5240A2 ● 40122
SIRLX1FMS5110A3 ● 40083	SIRLX2FMS51224DA3 ● 40103	SIRLX2FMS5240A3 ● 40123
SIRLX1FMS5110A4 ● 40084	SIRLX2FMS51224DA4 ● 40104	SIRLX2FMS5240A4 ● 40124
SIRLX1FMS5110A5 ● 40085	SIRLX2FMS51224DA5 ● 40105	SIRLX2FMS5240A5 ● 40125
SIRLX1FMS5110A6 ○ 40086	SIRLX2FMS51224DA6 ○ 40106	SIRLX2FMS5240A6 ○ 40126



Kg. 0,87
BA Kg. 0,55



Linea acustico/luminosa . Acoustic/luminous range